



BAHRAIN
SWITZGEAR & LIGHTING INDUSTRIES

BASIC BATTEN FITTINGS

BB

MATERIAL SPECIFICATION

Description

Material & Finish.

1. Housing

Fabricated from CRCA sheet steel, white epoxy powder coated.

ACCESSORIES

1. Ballast

Vacuum pressure impregnated type.

2. Lamp Holder

Push fit type, body made of heat resistant polycarbonate & rotor of extremely high heat resistant PBT.

3. Starter Holder

Push fit type, made of heat resistant polycarbonate.

4. Starter

Glow type starter.

5. Internal wiring

PVC insulated, heat resistant solid conductor.

6. Terminal connector

3 Way, 6A, suitable for 6 Sqmm cable.

7. Capacitor

Metalised polypropylene capacitor. (in case of HPF)

OPTIONS

HPF, extra low ballast, electronic ballast, dimmable ballast, emergency power pack, silicon insulated wiring.

APPLICATIONS

This is general purpose luminaire, suitable for use in shops, supermarkets, schools, factories, workshops, stores etc.

OTHER FEATURES

1. Cable entry Through 20mm knockout.

2. Mounting system Suitable for surface mounting.

4. Degree of protection IP20.



MODEL	TYPE	No of Lamps	L	W	D
B5BB120	FTL18/20W	1	610	55	40
B5BB140	FTL36/40W	1	1220	55	40
B5BB220	FTL18/20W	2	610	55	40
B5BB240	FTL36/40W	2	1220	55	40
B5BB440	FTL36/40W	4	1220	200	40
B5BB165	FTL58/65W	1	1520	55	40
B5BB265	FTL58/65W	2	1520	55	40