



## EMERGENCY SELF-CONTAINED LUMINAIRE

EML

### MATERIAL SPECIFICATION

#### Description

Material & Finish.

#### 1. Housing

UV resistant polycarbonate.

#### 2. Diffuser

UV resistant polycarbonate, textured.



### ACCESSORIES

#### 1. Lamp Holder

Push fit type, body made of heat resistant polycarbonate & rotor of extremely high heat resistant.

#### 2. Internal Wiring

PVC insulated, heat resistant solid conductor.

#### 3. Terminal connector

3 Way, 6A, suitable for 6 Sqmm cable.

#### 4. Battery

High temperature Ni-Cd. Emergency Time 3 Hrs.

#### 5. Electronic circuit board


#### 6. LED Indicator.

### OTHER FEATURES

1. Cable entry  
Through 19mm Knockout.
2. Mounting System  
Suitable for surface/  
Ceiling mounting.
3. Maintenance  
Easy maintenance by  
removal of diffuser, gear  
tray.
4. Degree of protection  
IP 40

### APPLICATIONS

Offices, Banks, Schools, Conference halls, meeting rooms, hotels, waiting rooms, corridors & similar other applications where escape lighting is necessary in the event of power failure.



### OPTIONS

Maintained, Non maintained. The maintained luminaries are also available with EXIT Signs.

MODEL	TYPE	No of Lamps	
BEM18	T58W	1	Maintained
BEMN18	T58W	1	Non Maintained