



SINGLE / DOUBLE SIDED EXIT SIGN LUMINAIRE

EXIT

MATERIAL SPECIFICATION

Description

Material & Finish.

1. Housing

Fabricated from CRCA sheet steel, white epoxy powder coated.

ACCESSORIES

1. Lamp Holder

Push fit type, body made of heat resistant polycarbonate & rotor of extremely high heat resistant.

2. Internal Wiring

PVC insulated, heat resistant solid conductor.

3. Terminal connector

3 Way, 6A, suitable for 6 Sqmm cable.

4. Battery

High temperature Ni-Cd. Emergency Time 3 Hrs.

5. Electronic circuit board

6. LED Indicator



OTHER FEATURES

1. Cable entry
Through 20mm Knockout.
2. Mounting System
Suitable for surface/ Ceiling mounting.
3. Maintenance
Easy maintenance by removal of diffuser, gear tray.
4. Degree of protection
IP 20.

OPTIONS

Maintained, Non maintained. Different legend panels both in English & Arabic available.

APPLICATIONS

Exit signs are designed to direct & illuminate the 'Means of escape' and should be sited on all escape routes, at every intersection & change of direction on that route, near each stair case & at the terminal Exit. Single sided Exit signs are used in applications where the viewing direction is uni-directional.

MODEL	TYPE	No of Lamps	
BSEXITMS18	T8W	1	Maintained/Single
BSEXITMD18	T8W	1	Maintained/Double
BSEXITNMS8	T8W	1	Non Maintained/Single
BSEXITNMD8	T8W	1	Non Maintained/Double

