

**BSLI**

BAHRAIN

SWITCHGEAR & LIGHTING INDUSTRIES

HIGH BAY LUMINAIRE

MATERIAL SPECIFICATION

Description

Material & Finish.

1. Housing

Fabricated from CRCA sheet steel, epoxy powder coated.

2. Reflector

High purity aluminium anodised.

ACCESSORIES

1. Ballast

Vacuum pressure impregnated type.

2. Ignitor

Super imposed pulse ignitor/impuser ignitor.

3. Internal wiring

PVC insulated, heat resistant solid conductor.

6. Terminal connector

3 Way, 10A, suitable for 10 Sqmm cable.

7. Capacitor

Metalised polypropylene capacitor.
(in case of HPF)

OTHER FEATURES

1. Mounting system

Suitable for Ceiling/
Suspension mounting.

3. Maintenance

Easy maintenance by
removal of sheet cover.

4. Degree of protection

IP 44.
IP 55 – Enclosed.

5. Class

1

6. Holder

E40

OPTIONS

Anodised aluminium reflector with various kinds & lamp positions, provides precise optical control. Light distribution can be varied from narrow to broad depending on the mounting height.

APPLICATIONS

Suitable for lighting of industrial premises with either clean or moderately polluted environments (Open & enclosed versions respectively).

BSGB01**BSR01****BSGB02****BSR02****BSGB03**

MODEL	Lamp Watts	H
BSGB01 (GearBox)	250 H.P.M	260
BSGB02	400 H.P.M	210
BSGB03	150 H.P.S	300
Reflector		
BSR01		350
BSR02		400